


## Holedall Petroleum Style Couplings

### Applications

- Recommended for discharge and suction service; commonly used in the transfer of fuel to homes, airplanes, ships, etc.
- Intended for fuel delivery service, see page 598 for information on API 1529 certification

### Features

- Compact, lightweight, and streamlined to eliminate catching on curbs and shrubs
- Stems and ferrules are designed to be used together as a coupling system
- Stem is expanded to nominal I.D. of hose for a rigid, uniform, full-flow area
- All fittings have octagonal facets for tightening with a wrench; females in 1-1/2" and larger sizes have lugs for tightening
- Pre-lubricated for assembly
- Designed for internal expansion only
- Hand and electrically operated installation equipment is available; consult Dixon® for pricing and availability
- Working pressure varies with the size of the fitting, the size and construction of the hose, and the media being conveyed; consult Dixon for recommendations
- Do not interchange with other manufacturers 

### Material

- Male and female stems are machined from bar stock or solid brass forgings; ferrules are available in brass and stainless steel

### Holedall Male Couplings

| Size   | Thread | Brass Part #       |
|--------|--------|--------------------|
| 3/4"   | NPT    | H5192              |
| 1"     |        | H5212-A            |
| 1-1/4" |        | H5222-A            |
| 1-3/8" |        | H5272 <sup>1</sup> |
| 1-1/2" |        | H5232-A            |
| 2"     |        | H5242              |
| 2-1/2" |        | H5252              |
| 3"     |        | H5262              |
| 1"     | NST    | H5212NST           |
| 1-1/2" |        | H5232NST           |

<sup>1</sup> 1-3/8" stem has 1-1/2" thread



L


### Holedall Female Couplings

| Size   | Thread | Brass Part #            |
|--------|--------|-------------------------|
| 3/4"   | NPSH   | H5191-BU                |
| 1"     |        | H5211-A-BU              |
| 1-1/4" |        | H5221-A-BU              |
| 1-3/8" |        | H5271-BU <sup>1</sup>   |
| 1-1/2" |        | H5231-A-BU              |
| 2"     |        | H5241-BU                |
| 2-1/2" | NPSM   | H5251-A-BU <sup>3</sup> |
| 3"     |        | H5261 <sup>3</sup>      |
| 1"     | NST    | H5211NST                |
| 1-1/2" |        | H5231NST <sup>2</sup>   |

<sup>1</sup> 1-3/8" stem has 1-1/2" thread

<sup>2</sup> 1-1/2" NST requires special adapter, part # H5231NSTADT

<sup>3</sup> 2-1/2" and 3" parts have female NPSM thread



### Holedall Grooved Couplings

| Size   | Brass Part # |
|--------|--------------|
| 1"     | G5212        |
| 1-1/2" | G5232        |
| 2"     | G5242        |
| 2-1/2" | G5252        |

