



Series 1 Combination Units

Application:

- Units are intended for use in industrial compressed air systems only; not for use with fluids. Units must not be used where pressure or temperature may exceed maximum rated operating conditions.
- Combination Units are supplied with micro-fog lubricators.
-  The polycarbonated plastic bowls used on these units can be damaged and possibly burst if exposed to such substances as certain solvents, strong alkalis, compressor oils that contain ester-based additives or synthetic oils. Fumes of these substances in contact with the polycarbonate bowl, externally or internally, can also result in damage. Use metal bowl in applications where a plastic bowl might be exposed to substances that are incompatible with polycarbonates. Clean with warm water only.



Features:

- pressure range 5-125 PSI
- 1 oz. reservoir
- inlet pressure **150 PSI** maximum at ambient temperature (70°F)
- supplied with a GC620 gauge

Miniature Combination Units with Transparent Bowl

Port Size	Flow (SCFM)	Automatic Drain		Manual Drain	
		Part #	Price/E	Part #	Price/E
1/8"	14	P1A-100A	\$263.80	P1A-100M	\$254.05
1/4"	14	P1A-200A	261.00	P1A-200M	251.45




transparent bowls

F

Features:

- pressure range 5-150 PSI
- 2 oz. reservoir
- inlet pressure:
 - transparent bowl: **150 PSI** at ambient temperature (70°F)
 - metal bowl: **250 PSI** at ambient temperature (70°F)
- supplied with a GC620 gauge
- connected modularly
- Includes 2 clamps and wall mounting brackets # 4214-52, 2 clamps # 4214-51 and 2 NPT pipe adapters. See modular components on pages 255, 257 and 259 for other options.



Sub-Compact Combination Unit with Transparent Bowl

Port Size	Flow (SCFM)	Automatic Drain		Manual Drain	
		Part #	Price/E	Part #	Price/E
1/4"	36	E72-2A	\$518.60	E72-2M	\$458.35
3/8"	36	E72-3A	507.40	E72-3M	450.80



metal bowls

Sub-Compact Combination Unit with Metal Bowl


Port Size	Flow (SCFM)	Automatic Drain		Manual Drain	
		Part #	Price/E	Part #	Price/E
1/4"	36	E72-2A-MB	\$551.30	E72-2M-MB	\$490.65
3/8"	36	E72-3A-MB	538.75	E72-3M-MB	481.70

Features:

- 5-150 PSI range
- 4 oz. reservoir
- inlet pressure:
 - transparent bowl: **150 PSI** at ambient temperature (70°F)
 - metal bowl: **250 PSI** at ambient temperature (70°F)
- supplied with a G230 gauge
- connected modularly
- Includes 2 clamps and wall mounting brackets # 4314-52, 2 clamps # 4314-51 and 2 NPT pipe adapters #4315-01. See modular components on pages 255, 257 and 259 for other options.

Compact Combination Unit with Transparent Bowl

Port Size	Flow (SCFM)	Automatic Drain		Manual Drain	
		Part #	Price/E	Part #	Price/E
1/4"	70	E73-2A	\$643.70	E73-2M	\$569.60
3/8"	70	E73-3A	642.15	E73-3M	568.05
1/2"	70	E73-4A	641.25	E73-4M	568.35



metal bowls

Compact Combination Unit with Metal Bowl

Port Size	Flow (SCFM)	Automatic Drain		Manual Drain	
		Part #	Price/E	Part #	Price/E
1/4"	70	E73-2A-MB	\$660.70	E73-2M-MB	\$586.65
3/8"	70	E73-3A-MB	659.15	E73-3M-MB	585.10
1/2"	70	E73-4A-MB	661.50	E73-4M-MB	586.80



FRL's are designed for air service only, unless otherwise indicated.

SCFM ratings given at 90 PSIG inlet pressure.